

# PRESIDENT

# MARYLAND

www.president-electronics.com

## SPECIFICATIONS :

|                    |                                                   |
|--------------------|---------------------------------------------------|
| Type               | : 7/8 onde - wave ( $\lambda$ )                   |
| Impedance          | : 50 Ohm ( $\Omega$ )                             |
| Frequency          | : 26-28 MHz                                       |
| Polarization       | : Verticale - Vertical                            |
| Adjustable SWR (1) | : 1,1/1                                           |
| Gain               | : + 5 dBi                                         |
| Max. power (2)     | : 500 Watt P.E.P                                  |
| Band width (3)     | : 2400 kHz (240 cx)                               |
| Weight             | : 0,250kg                                         |
| Length             | : 1550 mm                                         |
| Base               | : Type "N"                                        |
| Boring diameter    | : $\phi$ 13 mm to $\phi$ 16 mm - Max. Torque: 4Nm |
| Whip               | : Acier/carbone - Steel/carbon                    |

(1) At Resonance Frequency

(2) Maximum applicable power during 3 minutes

(3) For SWR. = 2/1 (4 W. R.M.S.)



Art. N° AMMI121



Any under warranty expedition must be done to our factory in Barcelona - Spain, the only authorized to decide about the warranty application (an original proof of purchase sales receipt must be included).

# MADE IN EUROPE - SPAIN